

Please type a plus sign (+) inside this box → ☐

Approved for use through 09/30/2000. OMB 0651-0032  
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE  
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

# UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No. 500.37445CX1

First Inventor or Application Identifier Takeshi MAEDA et al

Title See 1 in Addendum

Express Mail Label No.

## APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:

Assistant Commissioner for Patents  
Box Patent Application  
Washington, DC 20231

1 ☒ \* Fee Transmittal Form (e.g., PTO/SB/17)  
(Submit an original and a duplicate for fee processing)

2 ☒ Specification [Total Pages 32]  
(preferred arrangement set forth below)

- Descriptive title of the Invention
- Cross References to Related Applications
- Statement Regarding Fed sponsored R & D
- Reference to Microfiche Appendix
- Background of the Invention
- Brief Summary of the Invention
- Brief Description of the Drawings (if filed)
- Detailed Description
- Claim(s)
- Abstract of the Disclosure

3 ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 6]

4. Oath or Declaration [Total Pages 2]

- a. ☐ Newly executed (original or copy)
- b. ☒ Copy from a prior application (37 C.F.R. § 1.63(d))  
(for continuation/divisional with Box 16 completed)
- i. ☐ DELETION OF INVENTOR(S)  
Signed statement attached deleting  
inventor(s) named in the prior application,  
see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).

\* NOTE FOR ITEMS 1 & 13 IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY  
FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT  
IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

5. ☐ Microfiche Computer Program (Appendix)

6. Nucleotide and/or Amino Acid Sequence Submission  
(if applicable, all necessary)

- a. ☐ Computer Readable Copy
- b. ☐ Paper Copy (identical to computer copy)
- c. ☐ Statement verifying identity of above copies

## ACCOMPANYING APPLICATION PARTS

7 ☐ Assignment Papers (cover sheet & document(s))

8. ☐ 37 C.F.R. § 3.73(b) Statement ☐ Power of  
(when there is an assignee) ☐ Attorney

9. ☐ English Translation Document (if applicable)

10. ☒ Information Disclosure ☐ Copies of IDS  
Statement (IDS)/PTO-1449 Citations

11. ☐ Preliminary Amendment

12. ☒ Return Receipt Postcard (MPEP 503)  
(Should be specifically itemized)

13. ☐ \* Small Entity ☐ Statement filed in prior application  
Statement(s) ☐ Status still proper and desired  
(PTO/SB/09-12)

14. ☐ Certified Copy of Priority Document(s)  
(if foreign priority is claimed)

15. ☐ Other: .....

16 If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment

☒ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No 09/366,641  
Prior application information. Examiner K. Chu Group / Art Unit: 2752

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

## 17. CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Label

020457

or ☐ Correspondence address below

(Insert Customer No. or Attach bar code label here)

Name

Address

City

State

Zip Code

Country

Telephone

Fax

Name (Print/Type)

Alan E. Schiavelli

Registration No. (Attorney/Agent)

32,087

Signature

Date

October 25, 2000

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231

Attachment to PTO/SB/05 (4/98) Utility Patent Application  
Transmittal

1. INFORMATION RECORDING METHOD, INFORMATION RECORDING MEDIUM  
AND INFORMATION RECORDING APPARATUS

<b>FEE TRANSMITTAL</b> <b>for FY 2000</b> <small>Patent fees are subject to annual revision. Small Entity payments <u>must</u> be supported by a small entity statement, otherwise large entity fees must be paid. See Forms PTO/SB/09-12. See 37 C.F.R. §§ 1.27 and 1.28</small>		<b>Complete if Known</b>	
		Application Number	
		Filing Date	
		First Named Inventor	
		Examiner Name	
		Group / Art Unit	
TOTAL AMOUNT OF PAYMENT		(\$) <b>710.00</b>	
		Attorney Docket No. <b>500.37445CX1</b>	

<b>METHOD OF PAYMENT (check one)</b>		<b>FEE CALCULATION (continued)</b>																																																																																																																																																																																					
<b>1.</b> <input type="checkbox"/> The Commissioner is hereby authorized to charge indicated fees and credit any overpayments to:  Deposit Account Number <b>01-2135</b>  Deposit Account Name  <input type="checkbox"/> Charge Any Additional Fee Required Under 37 CFR §§ 1.16 and 1.17		<b>3. ADDITIONAL FEES</b> <table border="1"><thead><tr><th>Large Entity Fee Code</th><th>Small Entity Fee Code</th><th>Fee (\$)</th><th>Fee (\$)</th><th>Fee Description</th><th>Fee Paid</th></tr></thead><tbody><tr><td>105</td><td>130</td><td>205</td><td>65</td><td>Surcharge - late filing fee or oath</td><td>0.00</td></tr><tr><td>127</td><td>50</td><td>227</td><td>25</td><td>Surcharge - late provisional filing fee or cover sheet</td><td>0.00</td></tr><tr><td>139</td><td>130</td><td>139</td><td>130</td><td>Non-English specification</td><td>0.00</td></tr><tr><td>147</td><td>2,520</td><td>147</td><td>2,520</td><td>For filing a request for reexamination</td><td>0.00</td></tr><tr><td>112</td><td>920*</td><td>112</td><td>920*</td><td>Requesting publication of SIR prior to Examiner action</td><td>0.00</td></tr><tr><td>113</td><td>1,840*</td><td>113</td><td>1,840*</td><td>Requesting publication of SIR after Examiner action</td><td>0.00</td></tr><tr><td>115</td><td>110</td><td>215</td><td>55</td><td>Extension for reply within first month</td><td>0.00</td></tr><tr><td>116</td><td>380</td><td>216</td><td>190</td><td>Extension for reply within second month</td><td>0.00</td></tr><tr><td>117</td><td>870</td><td>217</td><td>435</td><td>Extension for reply within third month</td><td>0.00</td></tr><tr><td>118</td><td>1,360</td><td>218</td><td>680</td><td>Extension for reply within fourth month</td><td>0.00</td></tr><tr><td>128</td><td>1,850</td><td>228</td><td>925</td><td>Extension for reply within fifth month</td><td>0.00</td></tr><tr><td>119</td><td>300</td><td>219</td><td>150</td><td>Notice of Appeal</td><td>0.00</td></tr><tr><td>120</td><td>300</td><td>220</td><td>150</td><td>Filing a brief in support of an appeal</td><td>0.00</td></tr><tr><td>121</td><td>260</td><td>221</td><td>130</td><td>Request for oral hearing</td><td>0.00</td></tr><tr><td>138</td><td>1,510</td><td>138</td><td>1,510</td><td>Petition to institute a public use proceeding</td><td>0.00</td></tr><tr><td>140</td><td>110</td><td>240</td><td>55</td><td>Petition to revive - unavoidable</td><td>0.00</td></tr><tr><td>141</td><td>1,210</td><td>241</td><td>605</td><td>Petition to revive - unintentional</td><td>0.00</td></tr><tr><td>142</td><td>1,210</td><td>242</td><td>605</td><td>Utility issue fee (or reissue)</td><td>0.00</td></tr><tr><td>143</td><td>430</td><td>243</td><td>215</td><td>Design issue fee</td><td>0.00</td></tr><tr><td>144</td><td>580</td><td>244</td><td>290</td><td>Plant issue fee</td><td>0.00</td></tr><tr><td>122</td><td>130</td><td>122</td><td>130</td><td>Petitions to the Commissioner</td><td>0.00</td></tr><tr><td>123</td><td>50</td><td>123</td><td>50</td><td>Petitions related to provisional applications</td><td>0.00</td></tr><tr><td>126</td><td>240</td><td>126</td><td>240</td><td>Submission of Information Disclosure Stmt</td><td>0.00</td></tr><tr><td>581</td><td>40</td><td>581</td><td>40</td><td>Recording each patent assignment per property (times number of properties)</td><td>0.00</td></tr><tr><td>146</td><td>690</td><td>246</td><td>345</td><td>Filing a submission after final rejection (37 CFR § 1.129(a))</td><td>0.00</td></tr><tr><td>149</td><td>690</td><td>249</td><td>345</td><td>For each additional invention to be examined (37 CFR § 1.129(b))</td><td>0.00</td></tr><tr><td colspan="5">Other fee (specify) _____</td><td>0.00</td></tr><tr><td colspan="5">Other fee (specify) _____</td><td>0.00</td></tr><tr><td colspan="5"><b>SUBTOTAL (3)</b></td><td><b>(\$) 0.00</b></td></tr></tbody></table>		Large Entity Fee Code	Small Entity Fee Code	Fee (\$)	Fee (\$)	Fee Description	Fee Paid	105	130	205	65	Surcharge - late filing fee or oath	0.00	127	50	227	25	Surcharge - late provisional filing fee or cover sheet	0.00	139	130	139	130	Non-English specification	0.00	147	2,520	147	2,520	For filing a request for reexamination	0.00	112	920*	112	920*	Requesting publication of SIR prior to Examiner action	0.00	113	1,840*	113	1,840*	Requesting publication of SIR after Examiner action	0.00	115	110	215	55	Extension for reply within first month	0.00	116	380	216	190	Extension for reply within second month	0.00	117	870	217	435	Extension for reply within third month	0.00	118	1,360	218	680	Extension for reply within fourth month	0.00	128	1,850	228	925	Extension for reply within fifth month	0.00	119	300	219	150	Notice of Appeal	0.00	120	300	220	150	Filing a brief in support of an appeal	0.00	121	260	221	130	Request for oral hearing	0.00	138	1,510	138	1,510	Petition to institute a public use proceeding	0.00	140	110	240	55	Petition to revive - unavoidable	0.00	141	1,210	241	605	Petition to revive - unintentional	0.00	142	1,210	242	605	Utility issue fee (or reissue)	0.00	143	430	243	215	Design issue fee	0.00	144	580	244	290	Plant issue fee	0.00	122	130	122	130	Petitions to the Commissioner	0.00	123	50	123	50	Petitions related to provisional applications	0.00	126	240	126	240	Submission of Information Disclosure Stmt	0.00	581	40	581	40	Recording each patent assignment per property (times number of properties)	0.00	146	690	246	345	Filing a submission after final rejection (37 CFR § 1.129(a))	0.00	149	690	249	345	For each additional invention to be examined (37 CFR § 1.129(b))	0.00	Other fee (specify) _____					0.00	Other fee (specify) _____					0.00	<b>SUBTOTAL (3)</b>					<b>(\$) 0.00</b>
Large Entity Fee Code	Small Entity Fee Code	Fee (\$)	Fee (\$)	Fee Description	Fee Paid																																																																																																																																																																																		
105	130	205	65	Surcharge - late filing fee or oath	0.00																																																																																																																																																																																		
127	50	227	25	Surcharge - late provisional filing fee or cover sheet	0.00																																																																																																																																																																																		
139	130	139	130	Non-English specification	0.00																																																																																																																																																																																		
147	2,520	147	2,520	For filing a request for reexamination	0.00																																																																																																																																																																																		
112	920*	112	920*	Requesting publication of SIR prior to Examiner action	0.00																																																																																																																																																																																		
113	1,840*	113	1,840*	Requesting publication of SIR after Examiner action	0.00																																																																																																																																																																																		
115	110	215	55	Extension for reply within first month	0.00																																																																																																																																																																																		
116	380	216	190	Extension for reply within second month	0.00																																																																																																																																																																																		
117	870	217	435	Extension for reply within third month	0.00																																																																																																																																																																																		
118	1,360	218	680	Extension for reply within fourth month	0.00																																																																																																																																																																																		
128	1,850	228	925	Extension for reply within fifth month	0.00																																																																																																																																																																																		
119	300	219	150	Notice of Appeal	0.00																																																																																																																																																																																		
120	300	220	150	Filing a brief in support of an appeal	0.00																																																																																																																																																																																		
121	260	221	130	Request for oral hearing	0.00																																																																																																																																																																																		
138	1,510	138	1,510	Petition to institute a public use proceeding	0.00																																																																																																																																																																																		
140	110	240	55	Petition to revive - unavoidable	0.00																																																																																																																																																																																		
141	1,210	241	605	Petition to revive - unintentional	0.00																																																																																																																																																																																		
142	1,210	242	605	Utility issue fee (or reissue)	0.00																																																																																																																																																																																		
143	430	243	215	Design issue fee	0.00																																																																																																																																																																																		
144	580	244	290	Plant issue fee	0.00																																																																																																																																																																																		
122	130	122	130	Petitions to the Commissioner	0.00																																																																																																																																																																																		
123	50	123	50	Petitions related to provisional applications	0.00																																																																																																																																																																																		
126	240	126	240	Submission of Information Disclosure Stmt	0.00																																																																																																																																																																																		
581	40	581	40	Recording each patent assignment per property (times number of properties)	0.00																																																																																																																																																																																		
146	690	246	345	Filing a submission after final rejection (37 CFR § 1.129(a))	0.00																																																																																																																																																																																		
149	690	249	345	For each additional invention to be examined (37 CFR § 1.129(b))	0.00																																																																																																																																																																																		
Other fee (specify) _____					0.00																																																																																																																																																																																		
Other fee (specify) _____					0.00																																																																																																																																																																																		
<b>SUBTOTAL (3)</b>					<b>(\$) 0.00</b>																																																																																																																																																																																		
<b>2. <input checked="" type="checkbox"/> Payment Enclosed:</b> <input type="checkbox"/> Check <input type="checkbox"/> Money Order <input checked="" type="checkbox"/> Other																																																																																																																																																																																							
<b>FEE CALCULATION</b>																																																																																																																																																																																							
<b>1. BASIC FILING FEE</b> <table border="1"><thead><tr><th>Large Entity Fee Code</th><th>Small Entity Fee Code</th><th>Fee (\$)</th><th>Fee (\$)</th><th>Fee Description</th><th>Fee Paid</th></tr></thead><tbody><tr><td>101</td><td>690</td><td>201</td><td>345</td><td>Utility filing fee</td><td>710.00</td></tr><tr><td>106</td><td>310</td><td>206</td><td>155</td><td>Design filing fee</td><td></td></tr><tr><td>107</td><td>480</td><td>207</td><td>240</td><td>Plant filing fee</td><td></td></tr><tr><td>108</td><td>690</td><td>208</td><td>345</td><td>Reissue filing fee</td><td></td></tr><tr><td>114</td><td>150</td><td>214</td><td>75</td><td>Provisional filing fee</td><td></td></tr><tr><td colspan="5"><b>SUBTOTAL (1)</b></td><td><b>(\$) 710.00</b></td></tr></tbody></table>		Large Entity Fee Code	Small Entity Fee Code	Fee (\$)	Fee (\$)	Fee Description	Fee Paid	101	690	201	345	Utility filing fee	710.00	106	310	206	155	Design filing fee		107	480	207	240	Plant filing fee		108	690	208	345	Reissue filing fee		114	150	214	75	Provisional filing fee		<b>SUBTOTAL (1)</b>					<b>(\$) 710.00</b>																																																																																																																																												
Large Entity Fee Code	Small Entity Fee Code	Fee (\$)	Fee (\$)	Fee Description	Fee Paid																																																																																																																																																																																		
101	690	201	345	Utility filing fee	710.00																																																																																																																																																																																		
106	310	206	155	Design filing fee																																																																																																																																																																																			
107	480	207	240	Plant filing fee																																																																																																																																																																																			
108	690	208	345	Reissue filing fee																																																																																																																																																																																			
114	150	214	75	Provisional filing fee																																																																																																																																																																																			
<b>SUBTOTAL (1)</b>					<b>(\$) 710.00</b>																																																																																																																																																																																		
<b>2. EXTRA CLAIM FEES</b> <table border="1"><thead><tr><th>Total Claims</th><th>Extra Claims</th><th>Fee from below</th><th>Fee Paid</th></tr></thead><tbody><tr><td>5</td><td>-20** = 0</td><td>18</td><td>0</td></tr><tr><td>2</td><td>-3** = 0</td><td>80</td><td>0</td></tr><tr><td colspan="4">Multiple Dependent</td><td>0</td></tr></tbody></table> <small>**or number previously paid, if greater, For Reissues, see below</small> <table border="1"><thead><tr><th>Large Entity Fee Code</th><th>Small Entity Fee Code</th><th>Fee (\$)</th><th>Fee (\$)</th><th>Fee Description</th></tr></thead><tbody><tr><td>103</td><td>18</td><td>203</td><td>9</td><td>Claims in excess of 20</td></tr><tr><td>102</td><td>78</td><td>202</td><td>39</td><td>Independent claims in excess of 3</td></tr><tr><td>104</td><td>260</td><td>204</td><td>130</td><td>Multiple dependent claim, if not paid</td></tr><tr><td>109</td><td>78</td><td>209</td><td>39</td><td>** Reissue independent claims over original patent</td></tr><tr><td>110</td><td>18</td><td>210</td><td>9</td><td>** Reissue claims in excess of 20 and over original patent</td></tr><tr><td colspan="5"><b>SUBTOTAL (2)</b></td><td><b>(\$) 0.00</b></td></tr></tbody></table>		Total Claims	Extra Claims	Fee from below	Fee Paid	5	-20** = 0	18	0	2	-3** = 0	80	0	Multiple Dependent				0	Large Entity Fee Code	Small Entity Fee Code	Fee (\$)	Fee (\$)	Fee Description	103	18	203	9	Claims in excess of 20	102	78	202	39	Independent claims in excess of 3	104	260	204	130	Multiple dependent claim, if not paid	109	78	209	39	** Reissue independent claims over original patent	110	18	210	9	** Reissue claims in excess of 20 and over original patent	<b>SUBTOTAL (2)</b>					<b>(\$) 0.00</b>																																																																																																																																	
Total Claims	Extra Claims	Fee from below	Fee Paid																																																																																																																																																																																				
5	-20** = 0	18	0																																																																																																																																																																																				
2	-3** = 0	80	0																																																																																																																																																																																				
Multiple Dependent				0																																																																																																																																																																																			
Large Entity Fee Code	Small Entity Fee Code	Fee (\$)	Fee (\$)	Fee Description																																																																																																																																																																																			
103	18	203	9	Claims in excess of 20																																																																																																																																																																																			
102	78	202	39	Independent claims in excess of 3																																																																																																																																																																																			
104	260	204	130	Multiple dependent claim, if not paid																																																																																																																																																																																			
109	78	209	39	** Reissue independent claims over original patent																																																																																																																																																																																			
110	18	210	9	** Reissue claims in excess of 20 and over original patent																																																																																																																																																																																			
<b>SUBTOTAL (2)</b>					<b>(\$) 0.00</b>																																																																																																																																																																																		

<b>SUBMITTED BY</b>		<b>Complete (if applicable)</b>	
Name (Print/Type)	Alan E. Schiavelli	Registration No. (Attorney/Agent)	32,087
Signature		Telephone	703-312-6600
		Date	October 25, 2000

**WARNING:**

Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

Burden Hour Statement. This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231  
DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS SEND TO Assistant Commissioner for Patents, Washington, DC 20231

## CROSS REFERENCE TO RELATED APPLICATION

This is a continuation of U.S. application Serial No. 09/366,641, filed August 4, 1999, the subject matter of which is incorporated by reference herein.

## 5 BACKGROUND OF THE INVENTION

The present invention relates to information recording methods and apparatuses which use a medium for recording information by irradiating an energy beam and more particularly, to an information recording method and medium which can exhibit excellent effects on a phase transition optical disk as well as to an information recording apparatus based on the information recording method.

10 In a related art method for performing recording and erasing operations over a rewritable recording film, for example, when an optical disk is used which has an exchange coupling two-layer film as a recording film as disclosed in U.S. Patent No. 5,475,657, or when a phase transition type optical disk recording film is used which can erase information at high speed by realizing crystallization in substantially the same time as a laser irradiation time for recording as disclosed in JP-A-62259229 (laid-open on November 11, 1987); the recording and erasing are carried out by changing energy of one energy beam to one of at least two levels higher than a reading power level, that is, by changing the energy of the energy beam to one of at least a high power level and an intermediate power level. This method is advantageous in that so-called overwriting (rewriting based on

overwriting) of recording new information while erasing existing information can be realized. Further, as disclosed in JP-A-62259229 and JP-A-3-185629 (laid-open on August 13, 1991), such a phenomenon that a recording mark becomes a tear drop shape can be suppressed (a backward width of the recording mark becomes larger than a forward width thereof) by changing the energy of an energy beam into one of three power levels, that is, high and intermediate levels and a level lower than the intermediate level.

In recent years, there has been put in practical use a DVD-RAM (digital video disk-random access memory) which uses a 120mm-diametered disk made of phase transition material and having a memory capacity of 2.6 GB on its one side. A recording control method employed in this example is as shown in Fig. 1 and is explained as DVD Specification for Rewritable Disc (DVD-RAM), Part 1, Physical Specifications, version 1.0 (July, 1997), Page PHX-9, Fig. F-1.

JP-A-63-48617 (laid-open on March 1, 1988) also discloses a method for changing an energy beam depending on a mark length (corresponding to a region length in a second state in claims at the time of its application) or on a space length (corresponding to a region length in a first state in claims at the time of its application).

Also disclosed in JP-A-8-287465 (laid-open on November 1, 1996) is a method for converting an energy beam to a multi-pulsed train depending on a mark length or a space length.

## SUMMARY OF THE INVENTION

Studies concerning achievement of a higher density of rewritable digital video disk (DVD-RAM) using a phase transition recording film have recently been advanced. With such an optical disk device as to perform mark edge recording over a phase transition recording film as in DVD-RAM, it is required for the purpose of avoiding mark shape distortion or missing of erasing recorded marks that an achieved temperature and a cooling rate in a record mode are substantially the same even in any outer edge of a region of a recording film melted for formation of a recording mark. However, methods proposed so far failed to satisfy the above condition sufficiently in their various recording waveforms and were limited in their achievable recording densities. Further, recording characteristics of information recording medium usually vary with medium manufacturers, manufacturing times and lots. Thus as it is desired to obtain higher density recording, it becomes more difficult to secure a recording compatibility therebetween.

In particular, in the case of a DVD-RAM having a recording capacity of 4.7GB higher in density than a DVD-RAM having a recording capacity of 2.6GB, when recording is carried out with the same spot diameter as in the 2.6GB DVD-RAM, compatibility with the 2.6GB DVD-RAM can be achieved more easily. However, as a linear density is increased with the same spot used, a spacing between positions at which two adjacent recording pulses are irradiated on the recording

medium becomes smaller than the spot diameter of a laser beam on the medium. Therefore, since light distribution is overlapped when compared with the 2.6GB case, it becomes necessary to prevent distortion of a recording mark shape caused by the overlapping. Moreover, when a space between recording marks is small, impossible separation between the marks with a reading beam spot causes a shift of a recording mark edge position of a reproduction signal waveform, it is also required to prevent such a shift. The edge position shifting way depends largely on the design of the recording medium, and the recording waveform suitable for a specific recording medium is not always suitable for another recording medium. In current circumstances, because of the increased linear density, the recording mark edge shift is increased by a mismatch between the recording medium and recording waveform to such a level as not to be negligible.

It is therefore an object of the present invention to provide a method and apparatus which can accurately record information with use of the same spot and can increase its density while attaining a compatibility. A related object of the present invention is to provide an information recording method, medium and apparatus which can stably record information on various sorts of recording media having different characteristics and also can easily secure a recording compatibility therebetween.

In order to attain the above objects, an information recording method, medium and apparatus which follow are used.

1) An information recording method wherein a single recording mark is formed on a recording medium with use of a train of a plurality of energy beam pulses, and any of a first case where a falling edge timing of a head pulse in the energy beam pulse train is substantially stationary while a rising edge timing thereof is varied and a second case where the rising and falling edge timings of the head pulse are varied, is used to record information on the basis of control data previously recorded on the recording medium.

2) An information recording apparatus which comprises an energy beam generator; a power adjustment mechanism for adjusting a power level of an energy beam generated by the energy beam generator; a holder mechanism for holding a recording medium; a movement mechanism for relatively moving the energy beam and the recording medium; a signal processing circuit for changing information to be recorded to the power level of the energy beam; first timing adjustment means for causing the power adjustment mechanism to control the energy beam generator to generate a train of a plurality of energy beam pulses from the generator, for substantially fixing a falling edge timing of a head pulse in the energy beam pulse train, and at the same time for changing a rising edge timing thereof on the basis of control data previously recorded on the recording medium at time of forming a single recording medium on the recording medium; and second timing adjustment means for changing the rising and falling edge timings of the head pulse.



3) An information recording method which includes at least one of methods 1 and 2 and uses a recording medium capable of forming a first state zone with a first power level of an energy beam and a second state zone with a second power level of the energy beam higher than the first power level, wherein the energy beam and the recording medium are relatively moved to irradiate the energy beam on the recording medium and to form the first and second state zones with predetermined lengths and with a predetermined spacing therebetween on the recording medium to record information on the recording medium, a third power level lower than the second power level is provided, and at the time of forming the second state zone having a specific length on the recording medium, a duration of the third power level is included as mixed in a duration of the second power level to convert the energy beam to a multi-pulsed train and to irradiate the energy beam on the recording medium, the method 1 substantially fixes a falling edge position of a head pulse in the multi-pulsed train and moves a rising edge position thereof at the time of forming the second state zone having a specific length, the method 2 substantially fixes a rising edge position of a tail pulse of the multi-pulsed train and moves a falling edge position thereof at the time of forming the second state zone having the specific length, a fourth power level equal to or lower than the first power level is provided, the power level of the energy beam following the tail pulse of the multi-pulsed train is kept at the fourth

power level for a predetermined time and then kept at the first power level, and a time during which the fourth power level is kept is always constant regardless of the falling edge position of the tail pulse.

5           Since the above recording methods set forth in the above 1) and 2), information recording apparatus and corresponding information recording media are employed, the timing adjustment means always suitable for the information recording medium can be selected and information can be recorded therein always stably.

10           Since the above recording method of the above 3) is used, the time during which the constant fourth power level is maintained can be always realized for the information recording medium regardless of the timing adjustment.

15           Therefore, since thermal conditions always optimum for the information recording medium can be maintained, information can be recorded in the medium always stably.

20           Explanation will be made as to methods, apparatuses and recording media for recording information always stably in connection with embodiments which follow.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 shows how to record information in a recording strategy to which the present invention is applied;

25           Figs. 2A and 2B show experimental results in a case 2 in the recording strategy to which the present invention is applied;

Figs. 3A and 3B show experimental results in a case 2 in the recording strategy to which the present invention is applied;

5 Figs. 4A and 4B show experimental results in a case 1 in the recording strategy to which the present invention is applied;

Figs. 5A and 5B show experimental results in the case 1 in the recording strategy to which the present invention is applied; and

10 Fig. 6 shows specific examples of an information recording medium and apparatus to which the present invention is applied.

#### DESCRIPTION OF THE EMBODIMENTS

15 Explanation will be first be made as to reference numerals used herein.

Reference numeral 100 denotes a recording medium, 108 a casing, 110 a motor, 111 a rotary shaft, 112 a chucking mechanism, 115 a rail, 116 a rail guide, 117 a case, 118 a rotating motor, 119 a linear gear, 120 a rotary gear, 121 a magnet, 122 a coil, 123 a suspension, 130 an objective lens, 131 semiconductor laser, 132 a collimating lens, 133 a beam splitter, 134 a detection lens, 135 a photodetector, 140 a detector, 141 a detection switch, 150 a system controller, 151 a servo controller, 152 a amplifier, 153 a decoder, 153 a decoder, 154 a signal processing circuit, 155 a timing controller or delay circuit, 156 a current sink, 157 a constant or fixed current controller, 158 a output connector,

20  
25

159 an input connector, 160 a terminal, 161 a signal processing circuit.

The present invention will next be explained in accordance with embodiments which follow.

5 Shown in Fig. 1 are variations with time in the power level of an energy beam irradiated on a recording medium at the time of recording information on the recording medium. In this embodiment, how to change the power level at the time of recording information with time is referred to generally as write or recording strategy. Fig. 1 shows a recording strategy including an information recording method of the present invention. The present embodiment will be explained in connection with a DVD-RAM as a specific example. In the case of the DVD-RAM, assuming that a reference clock in recording and reproduction modes has a time width  $T_w$ , then the shortest mark and/or space has a length of  $3T_w$  (time length of 3 times as long as the time  $T_w$ ), and the longest mark and/or space has usually a length of  $11t_w$  and in a special case, of  $14T_w$ .

20 When an NRZI signal as information is given to be recorded on the recording medium in a time series manner, a suitable signal processing circuit converts the NRZI signal to a time series variation in the power level of an energy beam, which variation is shown in Fig. 1 as an light pulse waveform.

25 The power level is set to have 4 levels of write level, bias level 1, bias level 2 and bias level 3. At the bias level 1, the state of the recording medium having the energy beam

applied thereat can be placed in a first state; while at the write level, the recording medium can be placed in a second state. The bias level 3 is set to be equal to or lower than the bias level 1, when it is desired to form a second state area or zone in the recording medium and the second state area has a length of  $4T_w$  or more (that is, the NRZI signal has a length of  $4T_w$  or more), a duration having the power level of the bias level 3 is mixedly placed in the irradiation period of the write level to change the energy beam in a multi-pulsed form. In the multi-pulsed energy beam, the first and last light pulses are referred to as the head or first and tail or last pulses respectively. Between the head and tail pulses, light pulses are repeated between the write level and bias level 3. The repetition frequency, when the NRZI signal has a length of  $n$  ( $n > 3$ ), becomes  $(n-4)$ . The entire repetitive pulses between the head and tail pulses will be generally called a comb-shaped pulse. Accordingly, when it is desired to form a second state area for the NRZI signal having a length of  $5T_w$  or more, the recording pulse is made up of the head, comb-shaped and tail pulses. When it is desired to form a second state area for the NRZI signal having a length of  $4T_w$ , the recording pulse is made up of the head and tail pulses. When it is desired to form a second state area for the NRZI signal having a length of  $3T_w$ , the recording pulse is made up of a single pulse.

A power level equal to or lower than the bias level 1 and equal to or higher than the bias level 3 is set and is

referred to as the bias level 2. Following the tail pulse for  $4T_w$  or more and following the write light pulse for  $3T_w$ , the power level of the energy beam is held at the bias level 2 for a predetermined time.

5           There is possibility that the bias level 2 is equal to either one of the bias levels 1 and 3. Or there is possibility that the write level and bias levels 2 and 3 are all exactly at the same power level. There is a case where reference values of the write level and bias levels 1, 2 and 3  
10           are previously recorded at suitable locations on the recording medium as medium information. In this case the locations of the recording medium where the medium information relating to the recording strategy is recorded are referred to as information tracks for a control data zone. The reference  
15           values of the power levels are read out from the information tracks of the control data zone on the recording medium to determine each power level in a write mode.

          Consider in Fig. 1 a case where it is desired to form a second state area on the recording medium for the NRZI signal  
20           having a length of  $4T_w$  or more and to define a recording waveform. A time elapsed by  $T_{EFP}$  from a rising edge of the NRZI signal defines a falling edge of the head pulse in a write pulse train. Further, a rising edge of the head pulse is present at a time earlier by a time  $T_{FP}$  from file falling  
25           edge of the head pulse. This naturally means that, if the elapsed time from the rising edge of the NRZI signal to the rising edge of the head pulse is defined as  $T_{SFP}$ , the

relationship between  $T_{EFP}$ ,  $T_{SFP}$  and  $T_{FP}$  becomes  $T_{EFP} = T_{SFP} + T_{FP}$ .

A rising edge of the tail pulse in the write pulse train is present at a time elapsed by a time  $T_{SLP}$  from a reference time earlier by a time  $2T_w$  than a falling edge time of the NRZI signal. At a time elapsed by a time  $T_{ELP}$  from the rising edge time of the tail pulse, there is present a falling edge of the tail pulse. This naturally means that, if the elapsed time from the reference time earlier by a time  $2T_w$  than a falling edge of NRZI signal to the falling edge of the tail pulse is defined as  $T_{ELP}$ , the relationship between  $T_{SLP}$ ,  $T_{ELP}$  and  $T_{LP}$  becomes  $T_{ELP} = T_{SLP} + T_{LP}$ .

There may sometimes be present a comb-shaped pulse train between the head and tail pulses. Rising edges of pulses in the comb-shaped pulse train coincide with the position of the reference clock. At a time elapsed by the time  $T_{MP}$  from the rising edge time of each pulse, the pulse falls.

Consider a case where it is desired to form on the recording medium a second state area corresponding to the NRZI signal of  $3T_w$ . Assuming that a time elapsed by a time  $T_{EFP}$  from a rising edge of the NRZI signal is set as a reference time, then there exists a rising edge in a light pulse at a time earlier by the time  $T_{FP}$  from the reference time. This naturally means that, if the elapsed time from the rising edge of the NRZI signal to the rising edge of the light pulse is defined as  $T_{SFP}$ , the relationship between  $T_{EFP}$ ,  $T_{SFP}$  and  $T_{FP}$  becomes  $T_{EFP} = T_{SFP} + T_{FP}$ .

Further, when a time earlier by a time  $2T_w$  from the

falling edge time of the NRZI signal is set as a reference time and a time elapsed by the time  $T_{SLP}$  from the reference time is set as a second reference time, the light pulse falls at a time elapsed by a time  $T_{LP}$  from the second reference time.

5 This naturally means that, if the elapsed time from the reference time earlier by a time  $2T_w$  from a falling edge of NRZI signal to a falling edge of the light pulse is defined as  $T_{ELP}$ , the relationship between  $T_{SLP}$ ,  $T_{ELP}$  and  $T_{LP}$  becomes  $T_{ELP}$ ,  $T_{SLP} + T_{LP}$ .

10 The last pulse of the NRZI signal of  $4T_w$  or more or the write pulse of the NRZI signal of  $3T_w$  is followed by a duration having a power level of the bias level 2 and having a time length of  $T_{LC}$ .

15 The reference values of the times  $T_{EFP}$ ,  $T_{SFP}$ ,  $T_{FP}$ ,  $T_{ELP}$ ,  $T_{SLP}$ ,  $T_{LP}$ ,  $T_{LC}$  and  $T_{MP}$  defining the write pulse are read out from the information track of the control data zone, and these times are determined based on the read-out reference values.

20 The times  $T_{EFP}$ ,  $T_{SFP}$ ,  $T_{FP}$ ,  $T_{ELP}$ ,  $T_{SLP}$ ,  $T_{LP}$ ,  $T_{LC}$  and  $T_{MP}$  defining the write pulse are not always limited to having their constant values and sometimes may be required to be changed depending on combinations of the NRZI signals. In particular, in the case of DVD-RAM having a memory capacity of 4.7GB per one side as an example, the NRZI signal of  $3T_w$  as the shortest mark has a length of about 0.42 microns that is shorter than a  
25 write spot diameter of 0.45 microns. When such high density recording is carried out, thermal interference between adjacent marks becomes great, which, in some cases, makes it



difficult to realize the recording always stably. To avoid this, it is considered to change the write waveform to a suitable form according to the combinations of the NRZI signals. In order to correct a shift in the leading edge, any of the times  $T_{\text{EFP}}$  and  $T_{\text{FP}}$  is changed. Changes in these times from the reference values thereof are referred to as  $\Delta T_{\text{EFP}}$  and  $T_{\text{TFP}}$  respectively.

If  $T_{\text{EFP}}$  is changed by  $\Delta T_{\text{EFP}}$  and  $T_{\text{FP}}$  is not changed,  $T_{\text{SFP}}$  changes by  $\Delta T_{\text{EFP}}$ . If  $T_{\text{FP}}$  is changed by  $\Delta T_{\text{FP}}$  and  $T_{\text{EFP}}$  is not changed,  $T_{\text{SFP}}$  changes by  $\Delta T_{\text{FP}}$ . These changes naturally come from the relationship of  $T_{\text{EFP}} = T_{\text{SFP}} + T_{\text{FP}}$ .

The changes can be described by the followings with completely the same meaning. In case  $T_{\text{EFP}}$  is changed without changing  $T_{\text{FP}}$ ,  $T_{\text{SFP}}$  is changed by  $\Delta T_{\text{SFP}}$  without changing  $T_{\text{FP}}$ . Then  $T_{\text{EFP}}$  is automatically changed by  $\Delta T_{\text{SFP}}$ . In case  $T_{\text{FP}}$  is changed without changing  $T_{\text{EFP}}$ ,  $T_{\text{SFP}}$  is changed by  $\Delta T_{\text{SFP}}$  without changing  $T_{\text{EFP}}$ . Then  $T_{\text{FP}}$  is automatically changed by  $-\Delta T_{\text{SFP}}$ .

The meaning of the two descriptions to correct a shift in the leading edge is completely equivalent. To avoid redundancy, only the first description is used in this embodiment. The second description is always applicable to the part in this embodiment where the first description is employed.

In order to correct a shift in the trailing edge, any of the times  $T_{\text{SLP}}$  and  $T_{\text{LP}}$  is changed. Changes in these times from the reference values thereof are referred to as  $\Delta T_{\text{SLP}}$  and  $\Delta T_{\text{LP}}$  respectively.

If  $T_{SLP}$  is changed by  $\Delta T_{SLP}$  and  $T_{LP}$  is not changed,  $T_{ELP}$  changes by  $\Delta T_{SLP}$ . If  $T_{LP}$  is changed by  $\Delta T_{LP}$  and  $T_{SLP}$  is not changed,  $T_{ELP}$  changes by  $\Delta T_{LP}$ . These changes naturally come from the relationship of  $T_{ELP} = T_{SLP} + T_{LP}$ .

5        The changes can be described by the followings with completely the same meaning. In case  $T_{SLP}$  is changed without changing  $T_{LP}$ ,  $T_{ELP}$  is changed by  $\Delta T_{ELP}$  without changing  $T_{LP}$ . Then  $T_{SLP}$  is automatically changed by  $\Delta T_{ELP}$ . In case  $T_{LP}$  is changed without changing  $T_{SLP}$ ,  $T_{ELP}$  is changed by  $\Delta T_{ELP}$  without changing  $T_{SLP}$ . Then  $T_{LP}$  is automatically changed by  $\Delta T_{ELP}$ .

10        The meaning of the two descriptions to correct a shift in the trailing edge is completely equivalent. To avoid redundancy, only the first description is used in this embodiment. The second description is always applicable to the part in this embodiment where the first description is employed.

15        A first lookup table of  $T_{MF}$  for the leading edge will be defined. The table is a list of values which are determined by combinations of a length  $M(n)$  of a mark being currently written and a length  $S(n-1)$  of a space precedent to the mark and which can be positive or negative. Next a second lookup table of  $T_{ML}$  for the trailing edge will be defined. This table is a list of values which are determined by combinations of the length  $M(n)$  of a mark being currently written and a length  $S(n+1)$  of a space subsequent to the mark and which can be positive or negative.

25        In a case 1, the value of  $T_{MF}$  is made equal to the value

of  $\Delta T_{FP}$  and the value of  $T_{ML}$  is also made equal to the value of  $\Delta T_{LP}$ . In this case, the values of  $T_{FP}$  and  $T_{LP}$  vary depending on combinations of the NRZI signals. That is, in the head pulse, its rising edge position varies while its falling edge position is stationary. In the tail pulse, on the other hand, its rising edge position is stationary while its falling edge position varies.

If the second description to correct a shift in the leading and the trailing edge is used, the description for case 1 is as follows. The value of  $T_{MF}$  is made equal to the value of  $T_{SFP}$  without changing the value of  $T_{EFP}$ . The value of  $T_{ML}$  is made equal to the value of  $T_{ELP}$  without changing the value of  $T_{SLP}$ . The meaning of this description is perfectly the same as the first one.

In a case 2, the value of  $T_{MF}$  is made equal to the value of  $\Delta T_{EFP}$  and the value of  $T_{ML}$  is made equal to the value of  $\Delta T_{LP}$ . In this case, the values of  $T_{EFP}$  and  $T_{LP}$  vary depending on combinations of the NRZI signals. That is, in the head pulse, its rising and falling edge positions vary at the same time. In the tail pulse, on the other hand, its rising edge position is stationary while its falling edge position varies.

In a case 3, the value of  $T_{MF}$  is made equal to the value of  $\Delta T_{FP}$  and also the value of  $T_{ML}$  is made equal to the value of  $\Delta T_{SLP}$ . In this case, the values of  $T_{FP}$  and  $T_{SLP}$  vary depending on combinations of the NRZI signals. That is, in the head pulse, its rising edge position varies while its falling edge position is stationary. In the tail pulse, on the other hand,

its rising and falling edge positions vary at the same time.

In a case 4, the value of  $T_{MF}$  is made equal to the value of  $\Delta T_{EFP}$  and also the value of  $T_{ML}$  is made equal to the value of  $\Delta T_{SLP}$ . In this case, the values of  $T_{EFP}$  and  $T_{SLP}$  vary depending on combinations of the NRZI signals. That is, in the head pulse, its rising and falling edge positions vary at the same time in the tail pulse, on the other hand, its rising and falling edge positions vary at the same time.

If the second description to correct a shift in the leading and trailing edges is used, the description for case 2 is as follows. The value of  $T_{MF}$  is made equal to the value of  $T_{SFP}$  without changing the value of  $T_{FP}$ . The value of  $T_{ML}$  is made equal to the value of  $T_{ELP}$  without changing  $T_{LP}$ . The meaning of this description is perfectly the same as the first one.

In a case 5, the value of  $T_{MF}$  is made equal to the value of  $\Delta T_{FP}$ . In this case, the value of  $T_{FP}$  varies depending on combinations of the NRZI signals. That is, in the head pulse, its rising edge position varies while its falling edge position is stationary.

In a case 6, the value of  $T_{MF}$  is made equal to the value of  $\Delta T_{EFP}$ . In this case, the value of  $T_{EFP}$  varies depending on combinations of the NRZI signals. That is, in the head pulse, its rising and falling edge positions vary at the same time.

In a case 7, the value of  $T_{ML}$  is made equal to the value of  $\Delta T_{LP}$ . In this case the value of  $T_{LP}$  varies depending on combinations of the NRZI signals. That is, in the tail pulse, its rising edge position is stationary while its

falling edge position varies.

In a case 8, the value of  $T$  is made equal to the ML value of  $\Delta T_{SLP}$ . In this case, the value of  $T_{SLP}$  varies depending on combinations of the NRZI signals. That is, in the tail pulse, its rising and falling edge positions vary at the same time.

The values included in the first and second lookup tables and information on selection of any of the cases 1 to 8 are determined by reading information written in the information track of the control data zone on the recording medium.

As has been explained above, since adaptive waveform changes based on the lookup tables are divided into the cases 1 to 8 and any of the cases is selected, the method of the present invention can advantageously cope with recording media having various characteristics and can record information always stably with good compatibility.

In the present embodiment, the first lookup table was defined to have  $4 \times 4$  cases of 4 sorts of  $M(n) \times 4$  sorts of  $S(n-1)$ . The second lookup table was defined to have  $4 \times 4$  cases of 4 sorts of  $M(n) \times 4$  sorts of  $S(n+1)$ . However, the size of the lookup table is not limited to the  $4 \times 4$  cases but may be set at any cases other than  $1 \times 1$  to realize the effects of the present invention. Further, although each of the first and second lookup tables forms a two-dimensional table in the present embodiment, it may advantageously be a three-dimensional table based on a combination of three parameters of  $S(n-1)$ ,  $M(n)$  and  $S(n+1)$  or may be

multi-dimensional table. The simplicity and/or complexity of the table may be suitably determined by various factors including characteristics of a recording medium and a demanded recording accuracy. When a DVD-RAM having a memory capacity of 4.7GB for one side is used as an example, its lookup table is desirably a two dimensional table having a size of about  $3 \times 3$ ,  $4 \times 3$ ,  $3 \times 4$  or  $4 \times 4$ .

Now explanation will be made as to mark edge controllability in connection with the cases 1 and 4 as an example. Several experimental results are shown herein. In this connection, their experimental conditions are set so that a linear speed is about 8m/sec., T is about 17nsec., a 3T mark as the shortest mark has a physical length of about  $0.4 \mu\text{m}$  or slightly more, a track pitch is about  $0.6 \mu\text{m}$ , a peak power is 11mW, the bias power 1 is 4.5mW, the bias power 2 is 3.5mW and the bias power 3 is 1mw.

A single mark having a specific length is recorded always under the same conditions, which is referred to as the anchor mark. Following a space (corresponding to an area having no recorded mark between adjacent recording marks) subsequent to the anchor mark, a mark to be measured (which will be sometimes referred to as the measurement mark) is recorded. A recording pulse for the measurement mark is controlled according to the above case 1 or 4. A reproduction signal obtained by reproducing the anchor mark and measurement mark is digitized into predetermined slice levels to obtain a binary data signal. The binary data signal is used to measure

a time interval (leading edge interval) from the leading edge of the anchor mark to the leading edge of the measurement mark. Further, the binary data signal is used to measure a time interval (trailing edge interval) from the trailing edge of the anchor mark to the trailing edge of the measurement mark.

Shown in Fig. 2A are variations in the leading edge interval and shown in Fig. 2B are variation in the trailing edge interval when the tail pulse position is stationary while the head pulse position varies in the case 4. In the drawings, their plus directions of axes are time advancing directions. In the drawings, the lengths of the measurement mark are used as parameters. In Fig. 2A, the head pulse position and mark leading edge position are in a nearly linearly proportional relationship. In Fig. 2B, on the other hand, as the head pulse position moves, the trailing edge correspondingly moves. A movement of the trailing edge amounts even to about 50% of a movement of the head pulse position.

Shown in Fig. 3A are variations in the trailing edge interval and shown in Fig. 3A are variation in the leading edge interval when the head pulse position is stationary while the tail pulse position varies in the case 4.

In the drawings, their plus directions of axes are time advancing directions. In the drawings, the lengths of the measurement mark are used as parameters. In Fig. 3A, the tail pulse position and mark trailing edge position are in a nearly

linearly proportional relationship. In Fig. 3B, on the other hand, as the tail pulse position moves, the leading edge correspondingly moves. A movement of the leading edge amounts even to about 50% of a movement of the tail pulse position.

5 Shown in Fig. 4A are variations in the leading edge interval and shown in Fig. 4B are variations in the trailing edge interval when the tail pulse rising and falling positions are stationary while the head pulse rising position varies in the case 1. In the drawings, their plus directions of axes  
10 are time advancing directions. In the drawings, the lengths of the measurement mark are used as parameters. In Fig. 4A, the head pulse rising edge position and mark leading edge position are in a nearly linearly proportional relationship. In Fig. 4B, on the other hand, even when the leading edge  
15 position of the head pulse moves, this causes substantially no remarkable movement of the mark trailing edge position at least in a range where the leading edge position of the head pulse less varies.

20 Shown in Fig. 5A are variations in the trailing edge interval and shown in Fig. 5B are variations in the leading edge interval when the rising and falling edge positions of the head pulse are stationary while the falling edge position of the tail pulse varies in the case 1.

25 In the drawings, their plus directions of axes are time advancing directions. In the drawings, the lengths of the measurement mark are used as parameters. In Fig. 5A, the tail pulse falling edge position and mark trailing edge position



are in a nearly linearly proportional relationship. In Fig. 5B, on the other hand, even when the trailing edge position of the tail pulse moves, this causes substantially no remarkable movement of the mark leading edge position at least in a range where the trailing edge position of the tail pulse less varies.

When comparison is carried out between the case 4 of Figs. 2A, 2B and 3A, 3B and the case 1 of Figs. 4A, 4B and 5A, 5B, it will be noted from the experimental results shown herein that the case 1 is more preferable with respect to the recording medium and recording strategy used in the experiments. This is because, in the case 1, the leading edge position of the record mark can be controlled independently only by the rising edge position of the head pulse in the recording pulse, and the trailing edge position of the recording medium can be controlled independently only by the falling edge position of the tail pulse in the recording pulse. The case 4 is more deteriorated in the control independency and more difficult in the control than the case 1.

Although the case 1 is more preferable than the case 4 with respect to the recording medium and recording strategy used in the experiments, there is a case where the case 4 is more preferable than the case 1 depending on the design of the recording medium. More specifically, in the case 1, the energy per se possessed by the head or tail pulse is increased or decreased, so that, when the energy of the head or tail

pulse is excessively increased, this results in deterioration of overwrite or cross-erase characteristics. In the case 4, on the other hand, since the energy possessed by the entire recording pulse train varies only slightly, there is no

5 likelihood of deterioration of such overwrite or cross-erase characteristics, it goes without saying that, when sufficient margins are given to overwrite or cross-erase characteristics in the design of the recording medium, there can be designed a recording medium without any possibility of deterioration of  
10 the overwrite or cross-erase characteristics even in the case.

Explanation will then be made as to another embodiment of the present invention with reference to Fig. 6 showing an information storage apparatus in the form of a block diagram. For the convenience of explanation, a recording medium 100 is  
15 illustrated as mounted in the information storage apparatus. For the purpose of storing information, the recording medium 100 is indispensable, but it may be dismounted from the information storage apparatus or be mounted thereinto as necessary.

20 In Fig. 6, a chucking mechanism 112 is mounted to a rotary shaft 111 of a motor 110 attached to a casing 108 so that the chucking mechanism 112 holds a recording medium 100.

The chucking mechanism 112 acts to hold the recording medium 100. The motor 110,, rotary shaft 111 and chucking  
25 mechanism 112 form a mechanism for relatively moving the recording medium 100 and an energy beam.

Mounted to the casing 108 is a rail 115. A rail guide

116 guided by the rail 115 is mounted to a case 117. Also mounted to the case 117 is a linear gear 119, to which a rotary gear 120 is mounted. Transmission of rotation of the rotating motor 118 mounted on the casing 108 to the rotary gear 120 causes linear movement of the case 117 along the rail 115. The linear movement is directed toward nearly the radial direction of the recording medium 100.

Mounted to the case 117 is a magnet 121. Also mounted to the case 117 is an objective lens 130 through a suspension 123 which can be moved only in two directions, that is, in a direction of nearly a normal of the recording surface of the recording medium 100 and in a nearly radial direction of the recording medium 100. Mounted onto the objective lens 130 is a coil 122 as nearly opposed to a magnet 121. When a current flows through the coil 122, its magnetic effect causes the objective lens 130 to be able to move in two directions of the direction of nearly a normal of the recording surface of the recording medium 100 and the nearly radial direction of the recording medium 100. The rail 115, rail guide 116, case 117, magnet 121, suspension 123, coil 122 and objective lens 130 form a mechanism which positions the energy beam at a predetermined position on the recording medium 100.

Mounted to the case 117 is a semiconductor laser 131 as an energy beam generator. The energy beam emitted from the semiconductor laser 131 passes through a collimating lens 132 and a beam splitter 133 and then through the objective lens 130. Part of the light emitted from the objective lens 130 is

reflected by the recording medium 100, passed through the objective lens 130, reflected by the beam splitter 133, condensed by a detection lens 134, and then an intensity of the reflected light is then detected by a photodetector 135.

5 More in detail, the photodetector 135 has a plurality of divided light receiving areas. Intensities of light detected on the respective areas are amplified and calculated by an amplifier 152 to detect information (servo signal) indicative of a relative positional relationship between a light spot  
10 focused by the objective lens 130 and the recording medium 100 as well as an information read signal. The servo signal is sent from the amplifier to a servo controller 151, whereas the read signal is sent from the amplifier to a decoder 153.

When the recording medium 100 is loaded into the  
15 information storage apparatus and the chucking mechanism 112 fixedly holds the recording medium 100, a detector 140 detects the presence of the medium and sends a signal indicative of the medium presence to a system controller 150. The system controller 150, when receiving the signal, controls the motor  
20 110 in such a manner that the recording medium 100 is rotated at a suitable rotational speed. The system controller 150 also controls a rotating motor 118 in such a manner that the case 117 is located at a suitable position. The system controller 150 also causes the semiconductor laser 131 to  
25 controllably emit light, and also causes a servo controller 151 to be operated so that the rotating motor 118 is driven or a current flows through the coil 123 to position the light spot

focused by the objective lens 130 at a predetermined position on the recording medium 100. The servo controller 151 then sends a signal indicative of the focused spot formed on the recording medium 100 to the system controller 150. The system controller 150, when receiving the signal, sends an instruction to a decoder 153 to decode the read signal therein. When a read track is not an information track in the control data zone, the system controller 150 sends an instruction to the servo controller 151 such that the focused spot is positioned at an information track in the control data zone. As a result of the above operation, the system controller 150 reads the information track of the control data zone and reads out medium information recorded therein.

Written in the information track of the control data zone are such recording strategy parameters as already explained in connection with Fig. 1. That is, the system controller 150 reads out from the recording medium 100 information on the recording power level, time relations between recording pulses, lookup table, and the adaptive control set to any of the cases 1 to 8. The system controller 150 writes these recording strategy parameters in a parameter table of a signal processing circuit 154, a parameter table of a timing controller or delay circuit 155, and a current sink parameter of current sinks 156. The operations of the cases 1 to 8 explained in Fig. 1 can be realized by changing the writing method into the table of the delay circuit 155 depending on the selection of the cases 1 to 8 or by switching switches of

a delay circuit 155. Incorporated in the delay circuit 155 are first to fourth timing adjusting means. Also incorporated in the delay circuit 155 is a first change-over mechanism for switching between the first and second timing adjusting means.

5 Further incorporated in the delay circuit 155 is a second change-over mechanism for switching between the third and fourth timing adjusting means.

The timing of the system controller 150 of reading the recording strategy parameters from the recording medium 100 and writing these parameters in the parameter table of the signal processing circuit 154, the parameter table of the delay circuit 155 and the current sink parameter of the current sinks 156 may be set only when the recording medium 100 is put in its writable state. For example, when the recording medium 100 is placed in its write protect state, as when a write protect switch provided on a case of the recording medium 100 is set at its write protect position or as when an upper-level controller of the information storage apparatus issues a write protect command; a series of operations such as the reading of the recording strategy parameters can be omitted. For the purpose of detecting a write protect switch, the detection switch 141 is mounted to the casing 108 and sends its detected signal to the system controller. In the recording protection mode, a preparation time taken after the loading of the recording medium 100 in the chucking mechanism 112 until the medium reaches its reproducible state can be shortened by stopping the reading of

the recording strategy parameters.

When receiving an information reproduction command from the upper-level controller through the input connector 159, the system controller 150 issues a command to the servo controller 151 to position the focused spot at a suitable position on the recording medium 100, a signal obtained from the photodetector 135 is decoded by the decoder 153 to obtain read information, and then the read information is sent from the decoder 153 through an output connector 158 to the upper-level controller.

When receiving an information write command and write information (to be written) from the upper-level controller via an input connector 159, the system controller 150 issues a command to the servo controller 151 to position the focused spot at a suitable position on the recording medium 100. Further, the write information is converted by the signal processing circuit 161 to an NRZI signal. The converted NRZI signal is converted by the signal processing circuit 154 to a suitable train of a plurality of pulses. The pulse train is passed through the delay circuit 155 and transmitted to the current sinks 156. In the illustrated example, the signal processing circuit 154 and signal processing circuit 161 form a signal processing circuit which converts the write signal to the recording pulse trains.

A fixed current controller 157 is connected to the semiconductor laser 131 so that a total of currents consumed by the semiconductor laser 131 and current sinks 156 has

always a constant value. The plurality of current sinks 156 are connected to the fixed current controller 157. Whether or not the current sinks 156 are operated to absorb the current depends on the signal generated by the signal processing circuit 154 and passed through the delay circuit 155. When the current sinks 156 are operated, a part of the current issued from the fixed current controller 157 is absorbed by the current sinks 156, resulting in reduction of a current flowing into the semiconductor laser 131. This causes the energy level of the energy beam emitted from the semiconductor laser 131 to be varied. The signal processing circuit 154 and delay circuit 155 realize such a recording strategy as shown in Fig. 1 when the plurality of current sinks 156 are operated with suitable timing.

For the above operation, power is externally supplied to the information storage apparatus via a terminal 160.

As has been explained in the foregoing, recording is carried out as modified according to the cases 1 to 8, so that, even when such high-density recording is carried out as the shortest mark length is the recording spot radius or less, the information recording can advantageously be carried out independently of the characteristics of the recording medium and with good compatibility and good stability. Further, since the present invention uses such a recording medium as to be able to record information about selection of any of the cases 1 to 8 in the information track of the control data zone on the recording medium, there is provided a recording medium



which can record information with a high density independently of fluctuations in recording characteristics of the information storage apparatus always with good stability and compatibility.

5           Further, since the information about selection of any of the cases 1 to 8 is read out from the recording medium 100 and is used to reflect it on the state of the information storage apparatus, there are provided a recording method and an information storage apparatus which can record information  
10 always with good stability, and compatibility and with a high density.

          In accordance with the foregoing embodiments, even when such high-density recording is carried out as the shortest recording mark length is the recording spot radius or less,  
15 information can be recorded on a recording medium independently of characteristics of the recording medium or on characteristics of the information storage apparatus, always with good compatibility and stability.

WHAT IS CLAIMED IS:

1. A recording medium which has at least one zone storing at least one lookup table comprising an edge shift value of leading and trailing recording pulses.

5 2. A recording medium according to claim 1, wherein a plurality of zones are provided.

3. A recording medium according to claim 1, wherein said lookup table is a list of values which are determined by combinations of a length  $M(n)$  of a mark being currently  
10 written and a length  $S(n-1)$  of a space precedent to the mark and which can be positive or negative.

4. A recording medium which is used for the information recording apparatus which has a plurality of timing adjusting means, said recording medium having at least one zone storing  
15 information indicative of which of said plurality of timing adjusting means would be used for.

5. A recording medium according to claim 4, wherein a plurality of zones are provided.

## ABSTRACT OF THE DISCLOSURE

A recording medium which has a zone or zones storing lookup tables comprising an edge shift value of leading and trailing recording pulses.

Fig 1




Fig.2A




Fig.2B




Fig.3A




Fig.3B




Fig.4A




Fig.4B




Fig.5A




Fig.5B







Fig. 6



Parameter	Value	Unit	Parameter	Value	Unit
$\alpha$	0.001		$\beta$	0.001	
$\gamma$	0.001		$\delta$	0.001	
$\epsilon$	0.001		$\zeta$	0.001	
$\eta$	0.001		$\theta$	0.001	
$\iota$	0.001		$\kappa$	0.001	
$\lambda$	0.001		$\mu$	0.001	
$\nu$	0.001		$\xi$	0.001	
$\omicron$	0.001		$\pi$	0.001	
$\rho$	0.001		$\sigma$	0.001	
$\tau$	0.001		$\upsilon$	0.001	
$\phi$	0.001		$\chi$	0.001	
$\psi$	0.001		$\omega$	0.001	
$\Omega$	0.001		$\Lambda$	0.001	
$\Upsilon$	0.001		$\Phi$	0.001	
$\Psi$	0.001		$\Xi$	0.001	
$\Theta$	0.001		$\Sigma$	0.001	
$\Pi$	0.001		$\Upsilon$	0.001	
$\Gamma$	0.001		$\Delta$	0.001	
$\Sigma$	0.001		$\Lambda$	0.001	
$\Delta$	0.001		$\Phi$	0.001	
$\Lambda$	0.001		$\Xi$	0.001	
$\Phi$	0.001		$\Sigma$	0.001	
$\Xi$	0.001		$\Upsilon$	0.001	
$\Sigma$	0.001		$\Delta$	0.001	
$\Upsilon$	0.001		$\Lambda$	0.001	
$\Delta$	0.001		$\Phi$	0.001	
$\Lambda$	0.001		$\Xi$	0.001	
$\Phi$	0.001		$\Sigma$	0.001	
$\Xi$	0.001		$\Upsilon$	0.001	
$\Sigma$	0.001		$\Delta$	0.001	
$\Upsilon$	0.001		$\Lambda$	0.001	
$\Delta$	0.001		$\Phi$	0.001	
$\Lambda$	0.001		$\Xi$	0.001	
$\Phi$	0.001		$\Sigma$	0.001	
$\Xi$	0.001		$\Upsilon$	0.001	
$\Sigma$	0.001		$\Delta$	0.001	
$\Upsilon$	0.001		$\Lambda$	0.001	
$\Delta$	0.001		$\Phi$	0.001	
$\Lambda$	0.001		$\Xi$	0.001	
$\Phi$	0.001		$\Sigma$	0.001	
$\Xi$	0.001		$\Upsilon$	0.001	
$\Sigma$	0.001		$\Delta$	0.001	
$\Upsilon$	0.001		$\Lambda$	0.001	
$\Delta$	0.001		$\Phi$	0.001	
$\Lambda$	0.001		$\Xi$	0.001	
$\Phi$	0.001		$\Sigma$	0.001	
$\Xi$	0.001		$\Upsilon$	0.001	
$\Sigma$	0.001		$\Delta$	0.001	
$\Upsilon$	0.001		$\Lambda$	0.001	
$\Delta$	0.001		$\Phi$	0.001	
$\Lambda$	0.001		$\Xi$	0.001	
$\Phi$	0.001		$\Sigma$	0.001	
$\Xi$	0.001		$\Upsilon$	0.001	
$\Sigma$	0.001		$\Delta$	0.001	
$\Upsilon$	0.001		$\Lambda$	0.001	
$\Delta$	0.001		$\Phi$	0.001	
$\Lambda$	0.001		$\Xi$	0.001	
$\Phi$	0.001		$\Sigma$	0.001	
$\Xi$	0.001		$\Upsilon$	0.001	
$\Sigma$	0.001		$\Delta$	0.001	
$\Upsilon$	0.001		$\Lambda$	0.001	
$\Delta$	0.001		$\Phi$	0.001	
$\Lambda$	0.001		$\Xi$	0.001	
$\Phi$	0.001		$\Sigma$	0.001	
$\Xi$	0.001		$\Upsilon$	0.001	
$\Sigma$	0.001		$\Delta$	0.	

E4715-c1  
Copy (\*)

# DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name, I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

"INFORMATION RECORDING METHOD, INFORMATION RECORDING

MEDIUM AND INFORMATION RECORDING APPARATUS"

the specification of which (check one)

☒

is attached hereto.

☐

was filed on \_\_\_\_\_  
as Application Serial No. \_\_\_\_\_  
and was amended on \_\_\_\_\_

(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

## Prior Foreign Application(s)

## Priority Claimed

10-220097

(Number)

Japan

(Country)

4 August, 1998

(Day/Month/Year Filed)

☒

Yes

☐

No

10-246744

(Number)

Japan

(Country)

1 Sep., 1998

(Day/Month/Year Filed)

☒

Yes

☐

No

(Number)

(Country)

(Day/Month/Year Filed)

☐

Yes

☐

No

(Number)

(Country)

(Day/Month/Year Filed)

☐

Yes

☐

No

(Number)

(Country)

(Day/Month/Year Filed)

☐

Yes

☐

No

(Number)

(Country)

(Day/Month/Year Filed)

☐

Yes

☐

No

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)

(Filing Date)

(Status: patented, pending, abandoned)

(Application Serial No.)

(Filing Date)

(Status: patented, pending, abandoned)

(Application Serial No.)

(Filing Date)

(Status: patented, pending, abandoned)

(Application Serial No.)

(Filing Date)

(Status: patented, pending, abandoned)

(Continued on Page 2)

I hereby appoint as principal attorneys; Donald R. Antonelli, Reg. No. 20,296; David T. Terry, Reg. No. 20,178; Melvin Kraus, Reg. No. 22,466; Stanley A. Wal, Reg. No. 26,432; William I. Solomon, Reg. No. 28,565; Gregory E. Montone, Reg. No. 28,141; Ronald J. Shore, Reg. No. 28,577; Donald E. Stout, Reg. No. 26,422; Alan E. Schiavelli, Reg. No. 32,087; James N. Dresser, Reg. No. 22,973 and Carl I. Brundidge, Reg. No. 29,621 to prosecute and transact all business connected with this application and any related United States application and international applications. Please direct all communications to the following address:

Antonelli, Terry, Stout & Kraus  
Suite 1800  
1300 North Seventeenth Street  
Arlington, Virginia 22209  
Telephone: (703) 312-6600  
Fax: (703) 312-6666

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further, that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United State Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

	(Full Name)	(Signature)
Date <u>July 21, 1999</u>	Inventor <u>Takeshi MAEDA</u>	<u>Takeshi Maeda</u>
Residence <u>Kokubunji-shi, Japan</u>	Citizenship <u>Japan</u>	
Post Office Address <u>5-4, Honcho-4-chome, Kokubunji-shi, Japan.</u>		
Date <u>July 21, 1999</u>	Inventor <u>Hirofumi SUKEDA</u>	<u>Hirofumi Sukeda</u>
Residence <u>Tokorozawa-shi, Japan</u>	Citizenship <u>Japan</u>	
Post Office Address <u>16-17, Higashitokorozawawada-1-chome, Tokorozawa-shi, Japan.</u>		
Date <u>July 21, 1999</u>	Inventor <u>Hiroyuki MINEMURA</u>	<u>Hiroyuki Minemura</u>
Residence <u>Kokubunji-shi, Japan</u>	Citizenship <u>Japan</u>	
Post Office Address <u>3-2-201, Higashikoigakubo-4-chome, Kokubunji-shi, Japan.</u>		
Date <u>July 21, 1999</u>	Inventor <u>Hidehiko KANDO</u>	<u>Hidehiko Kando</u>
Residence <u>Matsudo-shi, Japan</u>	Citizenship <u>Japan</u>	
Post Office Address <u>1292-1-901, Matsudo, Matsudo-shi, Japan.</u>		
Date <u>July 21, 1999</u>	Inventor <u>Makoto MIYAMOTO</u>	<u>Makoto Miyamoto</u>
Residence <u>Ome-shi, Japan</u>	Citizenship <u>Japan</u>	
Post Office Address <u>577-3-307, Chigasemachi-4-chome, Ome-shi, Japan.</u>		
Date _____	Inventor _____	
Residence _____	Citizenship _____	
Post Office Address _____		
Date _____	Inventor _____	
Residence _____	Citizenship _____	
Post Office Address _____		
Date _____	Inventor _____	
Residence _____	Citizenship _____	
Post Office Address _____		
Date _____	Inventor _____	
Residence _____	Citizenship _____	
Post Office Address _____		